



minipack®- torre
Packaging machines and systems

PLEXI 60

PACKAGING WITH CUSTOM CUTS AND NO WASTE



DESCRIPTION

PLEXI 60 is a fully automatic horizontal bagging machine with an extremely compact design and an innovative sealing system that packs up to 60 pieces per minute.

PLEXI 60 is not just a packaging machine for magazines. It can be combined with our **Tunnel 50 Twin** for shrinking together with electrostatic sealing, which means it can provide packaging for any product up to an A3 format (420 x 300 mm) and up to 32 mm high.

CD, video tapes, video games, components, publications, home care and food products, objects and medicines are just a few examples of application.

TECHNICAL FEATURES

minipack®-torre S.p.A.

Sede legale - Via Provinciale, 54 - 24044 DALMINE (BG) Italy

P.IVA - C.F.: 01633550163 - Capitale sociale 619.200,00 i.v. - Reg. Imprese di Bergamo 01633550163 - REA n. 224151



Electrical power supply	V	220
Phase	ph	1
MAX power installed	kW	1
Pneumatic supply	bar	4 - 6
Average pneumatic supply consumption	l/min	40
Hourly output	p/h (pph)	3600
MIN product size	mm	140x110
MAX product size	mm	420x300
Maximum product height	mm	32 (A3-A4) - 40 (A5-A6)
MAX Reel Strip dimensions (width)	mm	650
Machine dimensions	mm	2650x960x h. 1230
Machine weight (Net/Gross)	kg	499/549

minipack®-torre shall not be held liable for typos or printing errors in this catalogue. It also reserves the right to make changes to the specified features without prior notice. All trademarks are property of their respective owners and are hereby acknowledged.

PRODUCTIVITY

- o Production up to 60 pcs/min (up to an A4 format)
- o Easy to use.

VERSATILITY

- o Variety of materials that can be used: polyethylene, polyolefin, cartene plastic, polypropylene
- o Quick format changeover from the display
- o Machine with an extremely compact design.

COST-EFFECTIVE

- o Reduced investment for a high-performance machine
- o Use of flat reels (reels with more film)
- o No film waste (scrap) during production
- o Lower energy consumption (1 kW - 220 V).

minipack®-torre S.p.A.

Sede legale - Via Provinciale, 54 - 24044 DALMINE (BG) Italy

P.IVA - C.F.: 01633550163 - Capitale sociale 619.200,00 i.v. - Reg. Imprese di Bergamo 01633550163 - REA n. 224151



minipack®- torre
Packaging machines and systems

minipack®-torre S.p.A.

Sede legale - Via Provinciale, 54 - 24044 DALMINE (BG) Italy

P.IVA - C.F.: 01633550163 - Capitale sociale 619.200,00 i.v. - Reg. Imprese di Bergamo 01633550163 - REA n. 224151