Kompac EZ Koat Web 15

UV / Aqueous Coating System for On Demand Digital Labels



Change to Sheet Fed in Minutes!

Guaranteed to Cut Your Coating Electric Bill by 25%!*

Digital UV

Simplifying the Coating Business

- EZ to Set Up & Operate
- Apply UV, Aqueous, Specialty Coatings & Primers
- 2 Minute Coating Change & Clean Up!!
- **Digital Control Panel with Bulb Life Monitoring System**
- Variable Speed & UV Intensity Precise Curing / Saves Energy
- "Patented" Kompac Coating Unit
- **Automated Coating Fill System**
- **Runs Roll Stock or Sheets**
- Only 25 Amps!
- EZ One Stop Shopping for Coating & Supplies
- International Coating Support
- Environmentally Friendly



let Kompac put you in the coating business

FEATURES

Digital UV - A more **environmentally friendly** technology! Solid State UV replaces outdated & potentially hazardous ballast/mercury relay systems used in curing UV reactive inks and coatings.

The infinitely variable bulb control allows the operator to make precise adjustments resulting in the perfect curing wattage every time, whether digital or offset output, producing dramatic cost savings on power and excellent ROI!



Over curing can damage to digitally printed substrates causing the coating to "Scratch Off." Digital UV

- From 70 to 200 watts / inch Curing Power
- Instant Start-up
- Runs Cooler
- Compact & Light Weight
- Saves Energy (Guaranteed 25% Power Savings *)
- Eliminates Mercury
 (except for a minute amount used in the bulb)
- Kompac offers an "Ozone-Free Bulb" and a Recycling program for a greener operation

"Patented" Kompac Coating System

- EZ On/Off Coating Controls (Reduces Coating Waste)
- Produces the highest gloss and a perfect finish every time
- EZ to clean and change coatings With the patented
 "Kompac Vac" and our environmentally friendly UV
 Klean, coating change and clean up takes 2 minutes

SPECIFICATIONS

Sheet Size: 14.5", virtually any length 368mm, virtually any length

UV Lamp: Digital - variable UV Digital - variable UV
Speed: up to 80 feet / minute up to 24 meters / minute
Controls: Variable speed & UV
Stock Weight: 7pt. to 30pt. Digital - variable UV
Variable speed & UV
150g/m² to 600g/m²

Stock Weight: 7pt. to 30pt. 150g/m² to 600g/m² Dimensions: 72"L x 29"W x 50"H 1.8m x .75m x 1.3m

Weight: 400lbs. 181kgs.

Flectrical: 208-230/1Φ/50-60Hz/25A 208-230/1Φ/50-60Hz/25A

PERFECT FOR

- OKI pro511DW users
- APEX 1290 Users
- Digital Printers
- Switch from Roll to Roll to Sheet fed in minutes!
- Optimize / Prime your own substrates - Save \$\$

KOMPAC QUALITY


- Made in the USA!!
- Built Kompac tough for long life and productivity
- Celebrating over 33 years in Business
- (2) Year Warranty

GREAT SYSTEMS... GREAT SUPPORT!

- Kompac Komplete line of Coating & Cleaners
- One stop shopping
- Ask "The Coating Gurus"
 Our coating experts are
 available 7 days a week
 for your custom coating
 support.

Kompac Technologies, LLC 7 Commerce Street Somerville, NJ 08876 +1 908 534 8411 sales@kompactech.com

Kompac GmbH Siemensring 100 47877 Willich - Germany +49 2154 49010 europe@kompactech.com





^{*} Kompac EZ Koat will reduce your power consumption 25% compared to ballast type UV curing systems